

MMA 200



Parameter	Value
Input Voltage	AC220V±10% 1PH
Input Power (KVA)	6.94 KVA
Max Output Current (A)	200
VRD (V)	24V
Duty Cycle @ 40°C	200A @ 60%
No Load Voltage (V)	65V
Hot Start	YES
Protection & Insulation	IP 23S & H
Dimensions (mm)	383 x 190 x 330
Weight (kg)	6.5 kg

Key Features :

- 1.Do it Yourself:** Ideal for both professional and home-based welding projects, providing flexibility and ease of use.
- 2.Advanced IGBT Technology:** Core components utilize advanced IGBT inverter devices for stable output and high efficiency.
- 3.Intelligent Protection:** Equipped with overload and overheat protection, ensuring safe and reliable operation.
- 4.Self-adaptive Arc Force:** Automatically adjusts the arc force to provide smooth and easy welding performance.
- 5.Anti-Stick & Hot Start:** Ensures easy electrode removal and smooth arc initiation, even in challenging conditions.
- 6.VRD (Voltage Reduction Device):** Improves safety during welding and extends machine life by lowering the no-load voltage.
- 7.Stable & Reliable Performance:** Provides consistent performance, making welding enjoyable and efficient.
- 8.Auto Voltage Compensation:** Automatically compensates for voltage fluctuations, supporting a broader range of input voltages.

Optional Accessories



Cable length customize-able

- Rod holder with 25 mm 2 pure copper cable
- Earth clamp with 25 mm 2 pure copper cable



M.W.A. WELDING (THAILAND) CO., LTD.

68/88 หมู่ที่ 6 ตำบลเสาธงหิน อำเภอบางใหญ่ จังหวัดนนทบุรี 11140

โทร: 02-9030911-2 โทรสาร: 02-9030916

Email: mwathailand@hotmail.com